






















IP CAMERA 2MP		
Réf	Produit	Caracteristiques techniques
BS-52O12K		POE H.265, 2 Mp, 1/2.9 Progressive scan CMOS sensor 3,6mm DWDR IR 10-20m, Casing Aluminium IP67, ONVIF Profile S 2.6/ API, Video analytic
ES-52O12H		POE H.265, 2 Mp, 1/2.9 Progressive scan CMOS sensor 3,6mm DWDR IR 10-20m, Casing Aluminium IP67, ONVIF Profile S 2.6/ API, Video analytic
ES-52T12H		POE H.265, 2 Mp, 1/2.9 Progressive scan CMOS sensor 3,6mm WDR IR 10-20m, Casing Aluminium IP67, ONVIF Profile S 2.6/ API, starlight function , Video analytic
BS-52T12K		POE H.265, 2 Mp, 1/2.9 Progressive scan CMOS sensor 3,6mm WDR IR 10-20m, Casing Aluminium IP67, ONVIF Profile S 2.6/ API, starlight function , Video analytic
EL-52O28I		1/2,9 2MP Sony Low Light Sensor. H.265+ 3 flix Vidéo. IR 20-30m Farifocal 2,8-12mm Zoom motorisé 12X . Vidéo analytic IVA. POE. DWDR. IP67. ONVIF Profil S
DL-52O28B		1/2,9 2MP Sony Low Light Sensor. H.265+ 3 flix Vidéo. IR 20-30m Farifocal 2,8-12mm Zoom motorisé 12X . Vidéo analytic IVA. POE. DWDR. IP67. ONVIF Profil S
BL-52O28L		1/2,9 2MP Sony Low Light Sensor. H.265+ 3 flix Vidéo. IR 20-30m Farifocal 2,8-12mm Zoom motorisé 12X . Vidéo analytic IVA. POE. DWDR. IP67. ONVIF Profil S
PL-52C30A		2 Mp, H.265, 1/2.9" Low illumination CMOS 30X Zoom, WDR, Presets 255, Alarm I/O 1/1, IR Distance Up to 120m, IP66? ONVIF Profile S 2.6/ API
GT-SD682		2 MP, H.264, 1/3" low-light CMOS / 1/2.8" Exmor CMOS, IR distance 100m, 18X optional zoom, 255 preset positions, WDR, Alarm I/O 4-ch Input;2-ch Output, Aluminum , IP65, ONVIF Profile S 2.6/ API
BT-DA20K2-P		2.0 Mp ,1/2.7-inch Progressive scan CMOS sensor 4mm fixed lens, POE IR Distance : 20m
BT-BA20K4-P		2.0 Mp ,1/2.7-inch Progressive scan CMOS sensor 4mm fixed lens, POE avec support IR Distance : 50m
GT-BC520-P		2.0 Mp,1/3"SONY IMX122 Low Lux CMOS sensor 2.8-12mm Varifocal lens, hisilicon 3516C, POE



IP CAMERA 2MP

Réf	Produit	Caracteristiques techniques
GT-NR401-POE		4CH NVR 1 SATA Max 3TB, HDMI/VGA, RS485 Audio ouput: 1CH Support POE function
GT-NR401		4CH NVR 1 SATA Max 3TB, HDMI/VGA, RS485
GT-NR801		8CH NVR 1 SATA Max 3TB, HDMI/VGA, RS485
GT-NR1602		16CH NVR 2 SATA Max 6TB, HDMI/VGA, RS485 Audio input: 1CH, Audio ouput: 1CH
GT-NR3204		32CH NVR 4 SATA Max 12TB, HDMI/VGA, RS485 1 ESATA interface Alarm input: 16CH alarm output: 4CH

IP CAMERA 4MP		
Réf	Produit	Caracteristiques techniques
BS-54N12K		POE H.265, 4.0MP 1/3" Progressive Scan CMOS 3,6mm WDR IR 10-20m, Casing Aluminium IP67, ONVIF Profile S 2.6/ API, Video analytic
ES-54N12K		POE H.265, 4.0MP 1/3" Progressive Scan CMOS 3,6mm WDR IR 10-20m, Casing Aluminium IP67, ONVIF Profile S 2.6/ API, Video analytic
PT-DA294K2		4.0 Mp ,1/3-inch OV4689 CMOS sensor 4mm fixed lens, IR Distance : 2*Array LED 20m ONVIF Profile S 2.6/ API
PT-BA294K4		4.0 Mp ,1/3-inch OV4689 CMOS sensor 4mm fixed lens, avec support IR Distance : 4*Array LED 50m ONVIF Profile S 2.6/ API
Z504NE		4CH H.265 NVR 1 SATA Max 8TB non inclus, HDMI/VGA
Z508NE		8CH H.265 NVR 1 SATA Max 8TB non inclus, HDMI/VGA
Z5016NF		16CH H.265 NVR 2 SATA Max 8TB non inclus, HDMI/VGA Audio input: 1CH Audio output: 1CH
Z5032NM		32CH H.265 NVR 4 SATA 8TB Chacun non inclus, HDMI/VGA Audio input: 1CH Audio output: 1CH Alarm input: 16CH alarm output: 4CH
Z504NE-4P		4CH H.265 NVR 1 SATA Max 8TB non inclus, HDMI/VGA Support 4 port PoE
Z508NE-8P		8CH H.265 NVR 1 SATA Max 8TB non inclus, HDMI/VGA Support 8 port PoE
Z504NER		4CH H.265/H.264 NVR 5Mp 1 SATA Max 8TB non inclus, HDMI/VGA
Z508NER		8CH H.265/H.264 NVR 5Mp 1 SATA Max 8TB non inclus, HDMI/VGA
Z508NER-8P		8CH H.265/H.264 NVR 5Mp 1 SATA Max 8TB non inclus, HDMI/VGA. Switch 8 ports POE
Z516NER		16CH H.265/H.264 NVR 5Mp 1 SATA Max 8TB non inclus, HDMI/VGA
Z516NER-16P		16CH H.265/H.264 NVR 5Mp 1 SATA Max 8TB non inclus, HDMI/VGA. Switch 16 ports POE
Z532NHR		32CH H.265/H.264 NVR 5Mp 8 SATA Max 8TB non inclus, 1*Esata, HDMI/VGA, 3*USB 2.0, Alarm I/O 16/4, 2*RJ45 10M/100M/1000M